

PERFECT SOLUTIONS FOR **GAS ALARM** SYSTEMS



Technical Datasheet



PolyXeta®2

Sensor Head SSAX1

with Infrared Sensor for Methane or Propane

DESCRIPTION

APPLICATION

FEATURES

SPECIFICATIONS

ORDERING INFORMATION



Specifications subject to change without notice.
Up-to-date data sheets and user manuals can be found in the download area on www.msr-24.com.
PolyXeta® is a registered trademark of MSR-Electronic GmbH.
www.msr-electronic.de

■ All Products
■ Made
■ in Germany

DESCRIPTION

Sensor head with local bus interface and 5 m cable for remote connection to WSB2 sensor board series

In addition to the infrared sensor element and the measuring amplifier, the sensor head contains a μ Controller for processing the measured values. All relevant data and measured values of the sensor element are stored fail-safe in the μ Controller and are transmitted digitally via the local bus to the WSB2 board or output as a PWM signal. Calibration management is also integrated in the μ Controller of the sensor head.

Calibration can be performed by simply changing the sensor head or by the integrated, convenient calibration routine directly at the system.

APPLICATION

The PolyXeta®2 SSAX1 sensor head is used to monitor leaks in enclosed spaces classified as ATEX Zone 1 or Zone 2.

The WSB2 board used for evaluation is not suitable for installation in hazardous areas!

FEATURES

- ATEX and IEC Ex certificates for electrical explosion protection
- **SSAX1-1 for Zone 1 (can also be used in Zone 2):**
 - "Ex d" version with flameproof enclosure
- Continuous monitoring
- Low zero-point drift
- Sensor with long service life (5 years)
- High accuracy and reliability
- Easy calibration
- Calibration service by exchanging the sensor head
- Reverse polarity protected
- Overload protection
- Protection class IP65 with SplashGuard (see data sheet accessories)

SPECIFICATIONS

ELECTRICAL	
Power supply	5 VDC \pm 3 %: external limitation to 5.6 V with Z diode, > 2 W, required
Power consumption (at 24 V DC)	1 W, 200 mA, external limitation with 250 mA fuse (not resettable) required
INTERFACE	
Serial interface	1-wire / 19200 baud; MSR local bus protocol
PWM signal (option)	Frequency: 4 kHz (250 μ s); voltage swing 3.3 V: μ C Push-pull output in series with 10 k
SENSOR DATA	
Gas type	See Ordering Information
Sensor element	Infrared (NDIR)
Stabilization time	1 h
Warm-up time	30 s
Pressure range	Atmospheric \pm 10 % (influence + 1.5 % on measured value per kPa)
Storage temperature range	-40 °C to +70 °C (-40 °F to 158 °F)
Storage time	Max. 6 months
SENSOR HEAD HOUSING	
Material / colour	CrNi Stahl: 1.4404 / natural
Dimensions (d x H) mm	30 x 72 (+ ca. 27 for cable gland)
Weight	Ca. 0,25 kg
Protection class	IP54, with option splash proof IP65 (on request)
Installation	Vertical, gas inlet downwards
Cable gland, mounted	M25, Ex db approval
Max. tensile load	150 N
Cable with plug, factory assembled	Length 5 m to the remote WSB2 Board 3-pin standard plug for local bus version, 4-pin connector customer specific for PWM signal
Cable type	Li-YCY-10x 0,34 diameter min. 7,2 mm
ENVIRONMENTAL CONDITIONS	
Humidity	20 to 90 % RH (not condensing)
Operating temperature	-25 °C to +60 °C (-13 °F to 140 °F)
Storage temperature	-5 °C to +30 °C
Pressure range	800 to 1200 mbar (80 to 120 kPa)
ATEX MARKING	
Marking	Ex II 2G Ex db IIC T4 Gb, CE 0158
EC-type examination certificate	BVS 19 ATEX E 055 X (electrical Ex protection) Ex d; EN 60079-0, -1
Certificates	IECEX_BVS_19.0052X (electrical Ex protection) Ex d IEC 60079-0, -1
WARRANTY	
	1 year on sensor (not if poisoned or overloaded), 2 years on device

